


ROCKSHOX

Rear Shock Piston Tuning Guide

SIDLuxe / Deluxe / Deluxe Coil / Super Deluxe / Super Deluxe Coil
Vivid / Vivid Coil



TUNING GUIDE



SAFETY FIRST!

We care about YOU. Please, always wear your safety glasses and protective gloves when servicing RockShox products.

Protect yourself! Wear your safety gear!

⚠️ WARNING - PRESSURIZED DEVICE

Suspension products may contain pressurized air, nitrogen, springs, and oil.

Always wear certified safety glasses (ANSI Z87.1, EN166 EU) when performing any service on a suspension product (suspension fork, rear shock, seatpost). Failure to wear proper safety glasses can result in **SERIOUS INJURY OR DEATH**.

ROCKSHOX SERVICE	7
HOW TO USE THIS MANUAL.....	7
MODEL CODE IDENTIFICATION	8
WARRANTY AND TRADEMARK.....	8
SHIM MEASUREMENT	9
TUNE SHIM STACK HEIGHT TOLERANCE MEASUREMENTS - ORIGINAL AND REPLACEMENT.....	10
SIDLUXE (A1)	11
EXPLODED VIEW - SIDLUXE (A1).....	11
SIDLUXE (A1) REBOUND TUNES - L, M, H	12
SIDLUXE (A1) LOCK TUNES - 380, 430.....	13
SIDLUXE (A1) COMPRESSION TUNES - LC, L1, L	14
SIDLUXE (A1) COMPRESSION TUNES - M, H.....	15
SIDLUXE (A2)	16
EXPLODED VIEW - SIDLUXE (A2)	16
SIDLUXE (A2) REBOUND TUNES - R29, R57, R81.....	17
SIDLUXE (A2) REBOUND TUNES - R85, R87.....	18
SIDLUXE 3P (A2) MID-MODE TUNES - M2, M5, M8	19
SIDLUXE (A2) LOCK TUNES - X6, X8.....	20
SIDLUXE (A2) COMPRESSION TUNES - C25, C27, C30.....	21
SIDLUXE (A2) COMPRESSION TUNES - C33	22
SIDLUXE / SIDLUXE ISOSTRUT - FLIGHT ATTENDANT	23
EXPLODED VIEW - SIDLUXE FLIGHT ATTENDANT	23
SIDLUXE FLIGHT ATTENDANT - REBOUND TUNES - R29, R57	24
SIDLUXE FLIGHT ATTENDANT - MID-MODE TUNES - M2, M5, M8.....	25
SIDLUXE FLIGHT ATTENDANT - LOCK TUNES - X6, X8.....	26
SIDLUXE FLIGHT ATTENDANT - COMPRESSION TUNES - C25, C27, C30.....	27
SBC SIDLUXE WCID (A1)	28
EXPLODED VIEW - SBC SIDLUXE WCID (A1).....	28
SIDLUXE WCID (A1) REBOUND TUNES - R85.....	29
SIDLUXE WCID (A1) COMPRESSION TUNES - C24.....	30

SIDLUXE ISOSTRUT (A1)	31
EXPLODED VIEW - SIDLUXE ISOSTRUT (A1).....	31
SIDLUXE ISOSTRUT (A1) REBOUND TUNES - R81.....	32
SIDLUXE ISOSTRUT (A1) MID-MODE TUNES - M2, M5, M8.....	33
SIDLUXE ISOSTRUT (A1) LOCK TUNES - X6.....	34
SIDLUXE ISOSTRUT (A1) COMPRESSION TUNES - C27.....	35
DELUXE (B2)	36
EXPLODED VIEW - DELUXE ULTIMATE (B2).....	36
DELUXE ULTIMATE (B2) REBOUND TUNES - L, M.....	37
DELUXE ULTIMATE (B2) COMPRESSION TUNES - LC, L1, L.....	38
DELUXE ULTIMATE (B2) COMPRESSION TUNES - M, H.....	39
EXPLODED VIEW - DELUXE ULTIMATE REMOTE (B2).....	40
DELUXE ULTIMATE REMOTE (B2) REBOUND TUNES - L, M, H.....	41
DELUXE ULTIMATE REMOTE (B2) LOCK TUNES - 380, 430.....	42
DELUXE ULTIMATE REMOTE (B2) COMPRESSION TUNES - L1, L, M, H.....	43
EXPLODED VIEW - DELUXE SELECT+ (B2).....	44
DELUXE SELECT+ (B2) REBOUND TUNES - L, M, H, LINEAR (LN).....	45
DELUXE SELECT+ (B2) COMPRESSION TUNES - LC, L1, L.....	46
DELUXE SELECT+ (B2) COMPRESSION TUNES - M, H.....	47
EXPLODED VIEW - DELUXE SELECT (B2).....	48
DELUXE SELECT (B2) REBOUND TUNES - L, M, H, LINEAR (LN).....	49
DELUXE SELECT (B2) COMPRESSION TUNES - LC, L1, L.....	50
DELUXE SELECT (B2) COMPRESSION TUNES - M, H.....	51
DELUXE (C1)	52
EXPLODED VIEW - DELUXE ULTIMATE (C1).....	52
DELUXE ULTIMATE (C1) REBOUND TUNES - LINEAR, LINEAR H, DIGRESSIVE.....	53
DELUXE ULTIMATE (C1) COMPRESSION TUNES - LC, L1, L.....	54
DELUXE ULTIMATE (C1) COMPRESSION TUNES - M, H, DIGRESSIVE.....	55
EXPLODED VIEW - DELUXE SELECT+ (C1).....	56
EXPLODED VIEW - DELUXE SELECT (C1).....	57
DELUXE SELECT+, SELECT (C1) REBOUND TUNES - LINEAR, DIGRESSIVE.....	58
DELUXE SELECT+, SELECT (C1) COMPRESSION TUNES - LC, L1, L.....	59
DELUXE SELECT+, SELECT (C1) COMPRESSION TUNES - M, H.....	60

DELUXE COIL (B1)	61
EXPLODED VIEW - DELUXE SELECT (B1)	61
DELUXE COIL (B1) REBOUND TUNES - LINEAR, PROGRESSIVE	62
DELUXE COIL (B1) COMPRESSION TUNES - LC, L1, L	63
DELUXE COIL (B1) COMPRESSION TUNES - M, H	64
 SUPER DELUXE (B2)	 65
EXPLODED VIEW - SUPER DELUXE (B2)	65
SUPER DELUXE (B2) REBOUND CHECK PLATE AND REBOUND CHECK SHIMS	66
SUPER DELUXE (B2) REBOUND TUNES - L, M, H	67
SUPER DELUXE (B2) REBOUND TUNES - LINEAR L (LNL), LINEAR M (LNM), LINEAR (LN)	68
SUPER DELUXE (B2) COMPRESSION TUNES - LC, L1, L	69
SUPER DELUXE (B2) COMPRESSION TUNES - M, H	70
 SUPER DELUXE (C1)	 71
EXPLODED VIEW - SUPER DELUXE (C1)	71
SUPER DELUXE (C1) REBOUND TUNES - LINEAR, LINEAR H, LINEAR L	72
SUPER DELUXE (C1) REBOUND TUNES - DIGRESSIVE, PROGRESSIVE	73
SUPER DELUXE (C1) COMPRESSION TUNES - LC, L1, L	74
SUPER DELUXE (C1) COMPRESSION TUNES - M, H	75
 SUPER DELUXE (C2)	 76
EXPLODED VIEW - SUPER DELUXE (C2)	76
SUPER DELUXE (C2) REBOUND CHECK TUNES - R25, R53, R55	77
SUPER DELUXE (C2) REBOUND CHECK TUNES - R85	78
SUPER DELUXE (C2) REBOUND TUNES - R25, R53, R55	79
SUPER DELUXE (C2) REBOUND TUNES - R85	80
SUPER DELUXE (C2) COMPRESSION TUNES - C26, C30, C34	81
SUPER DELUXE (C2) COMPRESSION TUNES - C37, C40, C43	82
 SUPER DELUXE COIL (A2)	 83
EXPLODED VIEW - SUPER DELUXE COIL (A2)	83
SUPER DELUXE COIL (A2) REBOUND CHECK PLATE AND REBOUND CHECK SHIMS	84
SUPER DELUXE COIL (A2) REBOUND TUNES - L, M, H	85
SUPER DELUXE COIL (A2) REBOUND TUNES - LINEAR L (LNL), LINEAR M (LNM), LINEAR (LN)	86
SUPER DELUXE COIL (A2) COMPRESSION TUNES - LC, L1, L	87
SUPER DELUXE COIL (A2) COMPRESSION TUNES - M, H	88

SUPER DELUXE COIL (B1)	89
EXPLODED VIEW - SUPER DELUXE COIL (B1)	89
SUPER DELUXE COIL (B1) REBOUND TUNES - LINEAR, PROGRESSIVE	90
SUPER DELUXE COIL (B1) COMPRESSION TUNES - LC, L1, L	91
SUPER DELUXE COIL (B1) COMPRESSION TUNES - M, H	92
VIVID (C1)	93
EXPLODED VIEW - VIVID (C1)	93
VIVID (C1) REBOUND CHECK TUNES - R23, R25, R53	94
VIVID (C1) REBOUND CHECK TUNES - R54, R55, R85	95
VIVID (C1) REBOUND TUNES - R23, R25, R53	96
VIVID (C1) REBOUND TUNES - R54, R55, R85	97
VIVID (C1) COMPRESSION TUNES - C22, C26	98
VIVID (C1) COMPRESSION TUNES - C30, C34, C37	99
VIVID (C1) COMPRESSION TUNES - C40, C43	100
VIVID ULTIMATE FLIGHT ATTENDANT (C1) COMPRESSION TUNES - C22, C26	101
VIVID ULTIMATE FLIGHT ATTENDANT (C1) COMPRESSION TUNES - C30, C34, C37	102
VIVID ULTIMATE FLIGHT ATTENDANT (C1) COMPRESSION TUNES - C40, C43	103
VIVID COIL (C1)	104
EXPLODED VIEW - VIVID COIL (C1)	104
VIVID COIL (C1) REBOUND CHECK TUNES - R23, R25, R53	105
VIVID COIL (C1) REBOUND CHECK TUNES - R54, R55, R85	106
VIVID COIL (C1) REBOUND TUNES - R23, R25, R53	107
VIVID COIL (C1) REBOUND TUNES - R54, R55, R85	108
VIVID COIL (C1) COMPRESSION TUNES - C22, C26	109
VIVID COIL (C1) COMPRESSION TUNES - C30, C34, C37	110
VIVID COIL (C1) COMPRESSION TUNES - C40, C43	111
VIVID COIL ULTIMATE FLIGHT ATTENDANT (C1) COMPRESSION TUNES - C22, C26	112
VIVID COIL ULTIMATE FLIGHT ATTENDANT (C1) COMPRESSION TUNES - C30, C34, C37	113
VIVID COIL ULTIMATE FLIGHT ATTENDANT (C1) COMPRESSION TUNES - C40, C43	114

RockShox Service

We recommend that you have your RockShox suspension serviced and tuned by a qualified bicycle mechanic. Servicing RockShox suspension requires knowledge of suspension components, as well as the use of specialized tools and lubricants/fluids. Failure to follow the procedures outlined in the service manual for your shock may cause damage to your component and void the warranty.

Visit www.sram.com/service for the latest RockShox Spare Parts catalog and technical information. For order information, please contact your local SRAM distributor or dealer. Information contained in this publication is subject to change at any time without prior notice. **Your product's appearance may differ from the pictures contained in this publication.**

 For recycling and environmental compliance information, please visit: www.sram.com/en/company/about/environmental-policy-and-recycling.

How to use this manual


Check with the frame manufacturer to confirm the tune used in your shock for your frame model, then identify the desired tune. Follow your rear shock's service manual instructions to the Piston Service Section in the manual, available at www.sram.com/service. Once the piston assembly has been removed from the damper shaft, follow the instructions below to access your compression and/or rebound tune. Use the following pages to lay out your shim stack to the desired tune.

For specific tune assembly and orientation, consult the exploded view diagram for your shock in the model-specific sections within this document.

Compression Tune Change: With the piston assembly on a small hex wrench or pick, remove the compression shims from the hex wrench/pick.




Piston assembly




Compression tune

Rebound Tune Change: With the piston assembly on a small hex wrench or pick, remove the compression shims and piston and set aside. Remove the rebound shims from the hex wrench/pick.



Piston and Rebound Tune




Rebound tune

Piston Assembly: Follow the layout for your desired tune on the following pages, then reassemble the piston assembly on the hex wrench/pick, starting from the bottom of the page.

On the small hex wrench or pick, reassemble the piston assembly in the following order: any check shims / check plate (if necessary); rebound tune, starting with smallest shims and working to largest shims against the piston; piston; compression tune, starting with largest shim against the piston and working to smallest shim. Install the piston assembly back onto the damper shaft.

Once you have reassembled the piston assembly, return to the service manual for your shock to continue service and rebuild.



Piston assembly reassembled



Piston assembly installed

Model Code Identification

Product model code and specification details can be identified with the serial number on the product. Model codes can be used to identify the product type, series name, model name, and product version associated with the production model year. Product details can be used to identify spare parts, service kit, and lubricant compatibility.

Model Code example: **RS-DLX-SEL-C1**

RS = Product Type - **Rear Shock**

DLX = Platform/Series - **Deluxe**

SEL = Model - **Select**

C1 = Version - (**C** - third generation, **1** - first iteration)

To identify the model code, locate the serial number on the product and enter it into the **Search by Model Name or Serial Number** field at www.sram.com/service.

Warranty and Trademark


For SRAM Warranty information, visit: www.sram.com/warranty.

For SRAM Trademark information, visit: www.sram.com/website-terms-of-use.

Shim measurement

Print this document out at 100% and check the ruler below with calipers or a ruler. Adjust your printer settings, as needed, until the ruler on the printed page is accurate.

Alternatively, shim diameter and thickness can be measured with calipers. Use calipers to verify the shim outer diameter and shim thickness.



Shim Inner Diameter (ID)



Shim Outer Diameter (OD)



Shim Thickness

Tune Shim Stack Height Tolerance Measurements - Original and Replacement

Tune Shim Stack Height Tolerance (mm) - Super Deluxe Ultimate, Select+, Select (C1), Deluxe Ultimate (C1), Super Deluxe Coil Ultimate, Select+, Select (B1) ONLY:

When the original tune shim stack is removed, measure the total shim stack height (all shims stacked in order) and write it down. Measure the new replacement tune shim stack before installation, and compare the two.

If a rebound and/or compression tune is changed, each individual shim stack (all shims in each tune, stacked in order), must measure equal to or greater than (but not greater than 0.05 mm) the original tune shim stack height. If the new shim stack height is less than, or greater than (+0.05 mm), the original stack height, the number of rebound adjustment clicks may not equal the original number of clicks.

To correct this, **pivot shims*** of a different thickness, used from the original shim stack, may be substituted for pivot shims in the new shim stack to get the new tune shim stack to measure within 0.05 mm tolerance of the original tune shim stack height. Pivot shims are the smallest outer diameter shims (10, 11, 13 mm OD) in the tune shim stack. See each tune section to identify eligible pivot shims (of varying thickness) that can be substituted to achieve the correct total stack height for each tune shim stack.

Super Deluxe C1: If the rebound tune is changed, the rebound check shim stack must also be changed to match. See the [Super Deluxe C1](#) tune section in this manual for more details.

Tune Shim Stack Height Example 1: If the original (Super Deluxe C1) Digressive rebound tune shim stack measures 2.15 mm, and the replacement Progressive rebound tune shim stack measures 2.1 mm, then total shim stack is within (0.05) tolerance. Stack height total equals the total thickness of all shims stacked in order. **Note: Smaller diameter shims may be nested within and between a shim with a larger inner diameter.

SUPER DELUXE C1	ORIGINAL REBOUND TUNE - DIGRESSIVE			NEW REBOUND TUNE - PROGRESSIVE			
SHIM	ID x OD x SHIM THICKNESS (mm)	QUANTITY	TOTAL SHIM STACK THICKNESS (mm)	ID x OD x SHIM THICKNESS (mm)	QUANTITY	TOTAL SHIM STACK THICKNESS (mm)	
PIVOT SHIM*	9 x 11 x 0.3	3	0.9*	9 x 11 x 0.2	2	0.4*	
TUNE SHIM	9 x 17 x 0.15	2	0.3	9 x 18 x 0.2	2	0.4	
TUNE SHIM	9 x 18 x 0.15	2	0.3	9 x 19 x 0.2	2	0.4	
TUNE SHIM	9 x 19 x 0.15	1	0.15	9 x 20 x 0.2	2	0.4	
TUNE SHIM	9 x 16 x 0.10	1	0.1	9 x 16 x 0.10	1	0.1	
TUNE SHIM**	16.4 x 19 x 0.25	1	0.25	16.4 x 19 x 0.2	1	0.2	
TUNE SHIM	9 x 20 x 0.15	1	0.15	9 x 20 x 0.2	1	0.2	
SHIM STACK HEIGHT TOTAL			2.15	SHIM STACK HEIGHT TOTAL			2.1



Tune Shim Stack Height Example 2: If the original (Deluxe C1) M Compression tune shim stack height measures 2.3 mm, and the replacement H Compression tune shim stack height measures 2.4 mm, then total shim stack height is greater than the original (+0.1 mm) and is not within tolerance (greater than 0.05 mm). Stack height total equals the total thickness of all shims stacked in order.

To correct this, reduce the total shim stack height by removing two 8 x 10 x 0.2 pivot shims from the new H Compression tune, and adding one 8 x 10 x 0.3 pivot shim from the original M Compression tune to the new H compression tune shim stack. The modified H Compression tune shim stack height now equals 2.3 mm, which equals the original M Compression tune 2.3 mm stack shim height.

DELUXE C1	ORIGINAL COMPRESSION TUNE - M			NEW COMPRESSION TUNE - H			NEW MODIFIED COMPRESSION TUNE - H				
SHIM	ID x OD x SHIM THICKNESS (mm)	QUANTITY	TOTAL SHIM STACK THICKNESS (mm)	ID x OD x SHIM THICKNESS (mm)	QUANTITY	TOTAL SHIM STACK THICKNESS (mm)	ID x OD x SHIM THICKNESS (mm)	QUANTITY	TOTAL SHIM STACK THICKNESS (mm)		
TUNE SHIM	8 x 20 x 0.2	1	0.2	8 x 20 x 0.2	1	0.2	8 x 20 x 0.2	1	0.2		
PIVOT SHIM*	8 x 10 x 0.3	3	0.9	8 x 10 x 0.2	2	0.4	8 x 10 x 0.2	0	0		
PIVOT SHIM*	8 x 10 x 0.2	1	0.2	8 x 10 x 0.3	2	0.6	8 x 10 x 0.3	3	0.9		
TUNE SHIM	8 x 17 x 0.2	1	0.2	8 x 17 x 0.2	1	0.2	8 x 17 x 0.2	1	0.2		
TUNE SHIM	8 x 20 x 0.2	1	0.2	8 x 20 x 0.2	1	0.2	8 x 20 x 0.2	1	0.2		
TUNE SHIM	8 x 24 x 0.2	3	0.6	8 x 24 x 0.2	4	0.8	8 x 24 x 0.2	4	0.8		
SHIM STACK HEIGHT TOTAL			2.3	SHIM STACK HEIGHT TOTAL			2.4	MODIFIED SHIM STACK HEIGHT TOTAL			2.3




SIDLuxe (A1)

RS-SIDL-ULT-A1 / RS-SIDL-SELP-A1

Exploded View - SIDLuxe (A1)


Refer to the exploded view images to reference part orientation and assembly order.




SIDLuxe (A1) Rebound Tunes - L, M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - L




Shim Quantity	x2	x5	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - M



Shim Quantity	x3	x4	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - H




Shim Quantity	x4	x3	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

SIDLuxe (A1) Lock Tunes - 380, 430


Print this page at 100% scale and use the shim stack specification guide below to arrange the lock tune shim order. Refer to the exploded view images to reference part orientation and assembly order. Lock tune specifications are for reference only. Do not modify the Lock Tune shim stack arrangement. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the piston.

*Reference *SIDLuxe (A1) Compression Tunes* for Compression Tune shim stack specifications.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Lock Tune - 380



Shim Quantity	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>

Lock Tune - 430



Shim Quantity	x2	x2	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.2</u>

SIDLuxe (A1) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the Lock Tune.

*Reference *SIDLuxe (A1) Lock Tunes* for Lock Tune shim stack specifications.

100 mm



Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

Compression Tune - LC



Shim Quantity	x1	x1	x1	x1		
Shim Thickness (mm)	<u>0.15</u>	<u>0.1</u>	<u>0.2</u>	<u>0.3</u>		

Compression Tune - L1



Shim Quantity	x1	x1	x1	x1		
Shim Thickness (mm)	<u>0.15</u>	<u>0.1</u>	<u>0.2</u>	<u>0.3</u>		

Compression Tune - L




Shim Quantity	x2	x1	x1		
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.3</u>		

SIDLuxe (A1) Compression Tunes - M, H


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the Lock Tune.

*Reference *SIDLuxe (A1) Lock Tunes* for Lock Tune shim stack specifications.




Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

Compression Tune - M



Shim Quantity	x3	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.3</u>

Compression Tune - H




Shim Quantity	x4	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>

SIDLuxe (A2)

RS-SIDL-ULT2-A2 / RS-SIDL-ULT3-A2 / RS-SIDL-SLP2-A2 / RS-SIDL-SLP3-A2

Exploded View - SIDLuxe (A2)


Refer to the exploded view images to reference part orientation and assembly order.




SIDLuxe (A2) Rebound Tunes - R29, R57, R81

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - R29




Shim Quantity	x1	x2	x2
Shim Thickness (mm)	<u>0.20</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - R57*



Shim Quantity	x1	x2	x1	x1
Shim Thickness (mm)	<u>0.10</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - R81




Shim Quantity	x2	x2	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.3</u>


SIDLuxe (A2) Rebound Tunes - R85, R87

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - R85



Shim Quantity	x1	x2	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

Rebound Tune - R87




Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>


SIDLuxe 3P (A2) Mid-Mode Tunes - M2, M5, M8

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Mid-Mode Tune - M2*




Shim Quantity **x1**
Shim Thickness (mm) **0.15**

Mid-Mode Tune - M5*



Shim Quantity **x1** **x1**
Shim Thickness (mm) **0.15** **0.15**

Mid-Mode Tune - M8*




Shim Quantity **x2**
Shim Thickness (mm) **0.15**

SIDLuxe (A2) Lock Tunes - X6, X8


Print this page at 100% scale and use the shim stack specification guide below to arrange the lock tune shim order. Refer to the exploded view images to reference part orientation and assembly order. Lock tune specifications are for reference only. Do not modify the Lock Tune shim stack arrangement. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the piston.

*Reference *SIDLuxe (A2) Compression Tunes* for Compression Tune shim stack specifications.


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Lock Tune - X6



Lock Tune - X8




SIDLuxe (A2) Compression Tunes - C25, C27, C30

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the Lock Tune.

*Reference *SIDLuxe (A2) Lock Tunes* for Lock Tune shim stack specifications.




Compression Tune - C25




Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.10</u>	<u>0.15</u>	<u>0.2</u>	<u>0.3</u>

Compression Tune - C27



Shim Quantity	x1	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

Compression Tune - C30




Shim Quantity	x2	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

SIDLuxe (A2) Compression Tunes - C33


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the Lock Tune.

*Reference *SIDLuxe (A2) Lock Tunes* for Lock Tune shim stack specifications.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C33




Shim Quantity	x3	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>

SIDLuxe / SIDLuxe IsoStrut - Flight Attendant

RS-SIDL-UFA-A2 / RS-SIDL-STFA-A2 / RS-SIDL-ISFA-A1

Exploded View - SIDLuxe Flight Attendant


Refer to the exploded view images to reference part orientation and assembly order.




SIDLuxe Flight Attendant - Rebound Tunes - R29, R57

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - R29



Shim Quantity	x1	x2	x2
Shim Thickness (mm)	<u>0.20</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - R57




Shim Quantity	x1	x2	x1	x1
Shim Thickness (mm)	<u>0.10</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>


SIDLuxe Flight Attendant - Mid-Mode Tunes - M2, M5, M8

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Mid-Mode Tune - M2




Shim Quantity **x1**
Shim Thickness (mm) **0.15**

Mid-Mode Tune - M5



Shim Quantity **x1** **x1**
Shim Thickness (mm) **0.15** **0.15**

Mid-Mode Tune - M8



Shim Quantity **x2**
Shim Thickness (mm) **0.15**


SIDLuxe Flight Attendant - Lock Tunes - X6, X8

Print this page at 100% scale and use the shim stack specification guide below to arrange the lock tune shim order. Refer to the exploded view images to reference part orientation and assembly order. Lock tune specifications are for reference only. Do not modify the Lock Tune shim stack arrangement. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the piston.


*Reference *SIDLuxe Flight Attendant Compression Tunes* for Compression Tune shim stack specifications.



Lock Tune - X6



Lock Tune - X8



SIDLuxe Flight Attendant - Compression Tunes - C25, C27, C30

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the Lock Tune.

*Reference *SIDLuxe Flight Attendant Lock Tunes* for Lock Tune shim stack specifications.



Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

Compression Tune - C25




Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.10</u>	<u>0.15</u>	<u>0.2</u>	<u>0.3</u>

Compression Tune - C27



Shim Quantity	x1	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

Compression Tune - C30




Shim Quantity	x2	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

SBC SIDLuxe WCID (A1)

RS-SIDL-WCID-A1

Exploded View - SBC SIDLuxe WCID (A1)


Refer to the exploded view images to reference part orientation and assembly order.




SIDLuxe WCID (A1) Rebound Tunes - R85

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Tune - R85




Shim Quantity	x4	x3	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>

SIDLuxe WCID (A1) Compression Tunes - C24

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C24





Shim Quantity	x1	x2	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.2</u>	<u>0.1</u>

SIDLuxe IsoStrut (A1)

RS-SIDL-TKIS-A1

Exploded View - SIDLuxe IsoStrut (A1)


Refer to the exploded view images to reference part orientation and assembly order.




SIDLuxe IsoStrut (A1) Rebound Tunes - R81

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Tune - R81




Shim Quantity	x2	x2	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.3</u>


SIDLuxe IsoStrut (A1) Mid-Mode Tunes - M2, M5, M8

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Mid-Mode Tune - M2




Shim Quantity **x1**
Shim Thickness (mm) **0.15**

Mid-Mode Tune - M5



Shim Quantity **x1** **x1**
Shim Thickness (mm) **0.15** **0.15**

Mid-Mode Tune - M8




Shim Quantity **x2**
Shim Thickness (mm) **0.15**

SIDLuxe IsoStrut (A1) Lock Tunes - X6

Print this page at 100% scale and use the shim stack specification guide below to arrange the lock tune shim order. Refer to the exploded view images to reference part orientation and assembly order. Lock tune specifications are for reference only. Do not modify the Lock Tune shim stack arrangement. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the piston.

*Reference *SIDLuxe IsoStrut (A1) Compression Tunes* for Compression Tune shim stack specifications.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Lock Tune - X6



Shim Quantity

x1

x1

x1

x1

x1

x1

Shim Thickness (mm)

0.2

0.3

0.2

0.3

0.1


0.1

SIDLuxe IsoStrut (A1) Compression Tunes - C27


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the Lock Tune.

*Reference *SIDLuxe IsoStrut (A1) Lock Tunes* for Lock Tune shim stack specifications.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C27




Shim Quantity	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>

Deluxe (B2)

RS-DLX-ULT-B2 / RS-DLX-ULTR-B2 / RS-DLX-SELP-B2 / RS-DLX-SEL-B2

Exploded View - Deluxe Ultimate (B2)


Refer to the exploded view images to reference part orientation and assembly order.




Deluxe Ultimate (B2) Rebound Tunes - L, M

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - L



Shim Quantity	x2	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - M




Shim Quantity	x3	x2
Shim Thickness (mm)	<u>0.1</u>	<u>0.2</u>

Deluxe Ultimate (B2) Compression Tunes - LC, L1, L


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).




Compression Tune - LC



Compression Tune - L1




Compression Tune - L




Deluxe Ultimate (B2) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - M




Compression Tune - H



Exploded View - Deluxe Ultimate Remote (B2)

Refer to the exploded view images to reference part orientation and assembly order.



Deluxe Ultimate Remote (B2) Rebound Tunes - L, M, H


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the compression tune on the following page.

100 mm




Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

Rebound Tune - L




Shim Quantity	x1	x3	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.3</u>

Rebound Tune - M



Shim Quantity	x1	x5
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>

Rebound Tune - H



Shim Quantity	x1	x4	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>

Deluxe Ultimate Remote (B2) Lock Tunes - 380, 430

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the lock tune shim to the left of the piston (compression side).


*Reference *Deluxe Ultimate Remote (B2) Compression Tunes* for compression tune shim stack specifications.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm



Lock Tune - 380




Shim Quantity

x3 **x1** **x1** **x1** **x1**

Shim Thickness (mm)

0.2 **0.3** **0.15** **0.2** **0.3**

Lock Tune - 430



Shim Quantity

x1 **x3** **x2** **x1**

Shim Thickness (mm)


0.2 **0.3** **0.15** **0.2**

Deluxe Ultimate Remote (B2) Compression Tunes - L1, L, M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the HF piston.

*Refer to *Deluxe Ultimate Remote (B2) Closed Compression Tunes* for closed compression tune shim stack specifications.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - L1



Shim Quantity	x3	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - L



Shim Quantity	x2	x1	x1	x1	x2
Shim Thickness (mm)	<u>0.3</u>	<u>0.1</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>

Compression Tune - M



Shim Quantity	x2	x1	x1	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>


Compression Tune - H



Shim Quantity	x2	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>

Exploded View - Deluxe Select+ (B2)

Refer to the exploded view images to reference part orientation and assembly order.



Deluxe Select+ (B2) Rebound Tunes - L, M, H, Linear (LN)


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm




Rebound Tune - L




Shim Quantity	x2	x1	x4	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.1</u>	<u>0.2</u>	<u>0.15</u>

Rebound Tune - M




Shim Quantity	x3	x4	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>

Rebound Tune - H



Shim Quantity	x4	x3	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>

Rebound Tune - Linear (LN)



Shim Quantity	x3	x4	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>

Deluxe Select+ (B2) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).



Compression Tune - LC



Shim Quantity	x1	x2	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L1



Shim Quantity	x2	x1	x1	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>


Compression Tune - L



Shim Quantity	x1	x1	x1	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>


Deluxe Select+ (B2) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).



Exploded View - Deluxe Select (B2)

Refer to the exploded view images to reference part orientation and assembly order.



Deluxe Select (B2) Rebound Tunes - L, M, H, Linear (LN)


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the compression tune on the following page.

100 mm



Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

Rebound Tune - L




Shim Quantity	x1	x3	x1	x1	x3	x1			x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>			<u>0.1</u>	<u>0.3</u>	

Rebound Tune - M




Shim Quantity	x1	x3	x3	x3	x1				x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.3</u>	<u>0.1</u>				<u>0.1</u>	<u>0.3</u>	

Rebound Tune - H



Shim Quantity	x1	x5	x1	x3	x1				x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.3</u>	<u>0.1</u>				<u>0.1</u>	<u>0.3</u>	

Rebound Tune - Linear (LN)



Shim Quantity	x1	x1	x6	x1	x2	x1				x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>				<u>0.1</u>	<u>0.3</u>	

Deluxe Select (B2) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm



Compression Tune - LC




Shim Quantity	x2	x1	x2
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>

Compression Tune - L1



Shim Quantity	x1	x1	x1	x1	x2
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>


Compression Tune - L



Shim Quantity	x1	x1	x2	x2	x2
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>

Deluxe Select (B2) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).




Deluxe (C1)

RS-DLX-ULT-C1 / RS-DLX-SELP-C1 / RS-DLX-SEL-C1

Exploded View - Deluxe Ultimate (C1)

Refer to the exploded view images to reference part orientation and assembly order.



Deluxe Ultimate (C1) Rebound Tunes - Linear, Linear H, Digressive


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune on the following page.

100 mm




Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

Rebound Tune - Linear




Shim Quantity	x2	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - Linear H



Shim Quantity	x2	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.15</u>	<u>0.3</u>

Rebound Tune - Digressive



Shim Quantity	x3	x2
Shim Thickness (mm)	<u>0.1</u>	<u>0.2</u>

Deluxe Ultimate (C1) Compression Tunes - LC, L1, L


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

100 mm




Inner Diameter (ID:mm)
Outer Diameter (OD:mm)


Compression Tune - LC



Compression Tune - L1



Compression Tune - L



Deluxe Ultimate (C1) Compression Tunes - M, H, Digressive


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)


100 mm




Compression Tune - M



Compression Tune - H




Compression Tune - Digressive




Exploded View - Deluxe Select+ (C1)

Refer to the exploded view images to reference part orientation and assembly order.



Exploded View - Deluxe Select (C1)


Refer to the exploded view images to reference part orientation and assembly order.




Deluxe Select+, Select (C1) Rebound Tuner - Linear, Digressive

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the compression tune on the following page.


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Tune - Linear




Rebound Tune - Digressive




Deluxe Select+, Select (C1) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - LC




Shim Quantity	x1	x1	x1	x2	x2	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L1



Shim Quantity	x2	x1	x1	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L




Shim Quantity	x1	x1	x1	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>


Deluxe Select+, Select (C1) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - M



Shim Quantity	x1	x1	x1	x1	x1	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>

Compression Tune - H




Shim Quantity	x1	x1	x1	x2	x2
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>

Deluxe Coil (B1)

RS-DLXC-SEL-B1

Exploded View - Deluxe Select (B1)


Refer to the exploded view images to reference part orientation and assembly order.




Deluxe Coil (B1) Rebound Tuner - Linear, Progressive

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the check nut. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - Linear



Shim Quantity	x4	x3	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - Progressive




Shim Quantity	x1	x1	x1	x3	x3	x2	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>


Deluxe Coil (B1) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - LC




Shim Quantity	x5	x2	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>

Compression Tune - L1



Shim Quantity	x4	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>

Compression Tune - L




Shim Quantity	x1	x2	x2	x2	x2	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.15</u>

Deluxe Coil (B1) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - M



Compression Tune - H




Super Deluxe (B2)

RS-SDLX-ULTR-B2 / RS-SDLX-ULT-B2 / RS-SDLX-ULDH-B2 / RS-SDLX-SELP-B2 / RS-DLX-SEL-B2

Exploded View - Super Deluxe (B2)

Refer to the exploded view images to reference part orientation and assembly order.




Super Deluxe (B2) Rebound Check Plate and Rebound Check Shims


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the corresponding rebound tune on the following page.

If switching rebound tunes, the rebound tune must be matched with the rebound check tune. For example, if a standard rebound tune (L, M, H) is changed to a linear rebound tune (LNL, LNM, LN), install a linear rebound check tune.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Check Tune for L, M, H Rebound Tunes



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>

Rebound Check Tune for Linear L (LNL), Linear M (LNM), Linear (LN) Rebound Tunes




Shim Quantity	x2
Shim Thickness (mm)	<u>0.15</u>

Super Deluxe (B2) Rebound Tunes - L, M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the rebound shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Stack the rebound tune shims onto a hex wrench/pick, starting with the rebound tune shim to the left of the rebound check plate (flat side). Then continue reassembly with the compression tune.

*Consult the *Super Deluxe (B2) Rebound Check Plate and Rebound Check Shims* section to identify the corresponding rebound check tune.




Super Deluxe (B2) Rebound Tunes - Linear L (LNL), Linear M (LNM), Linear (LN)


Print this page at 100% scale and use the shim stack specification guide below to arrange the rebound shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Stack the rebound tune shims onto a hex wrench/pick, starting with the rebound tune shim to the left of the rebound check plate (flat side). Then continue reassembly with the compression tune.

*Consult the *Super Deluxe (B2) Rebound Check Plate and Rebound Check Shims* section to identify the corresponding rebound check tune.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Tune - Linear L (LNL)




Shim Quantity	x3	x2	x2	x2	x2	x2	x1		
Shim Thickness (mm)	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.2</u>		

Rebound Tune - Linear M (LNM)



Shim Quantity	x3	x1	x1	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.15</u>	<u>0.3</u>	

Rebound Tune - Linear (LN)




Shim Quantity	x3	x2	x3	x1	
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	


Super Deluxe (B2) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - LC



Shim Quantity	x4	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L1



Shim Quantity	x1	x3	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L




Shim Quantity	x3	x2	x1	x1	x2
Shim Thickness (mm)	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>


Super Deluxe (B2) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - M



Shim Quantity	x2	x1	x2	x2	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - H



Shim Quantity	x2	x2	x3	x2
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>


Super Deluxe (C1)

RS-SDLX-UFA-C1 / RS-SDLX-ULT-C1 / RS-SDLX-ULDH-C1 / RS-SDLX-SELP-C1 / RS-SDLX-SEL-C1

Exploded View - Super Deluxe (C1)

Refer to the exploded view images to reference part orientation and assembly order.


Super Deluxe C1 (upgrade): If the Super Deluxe C2 High Flow Damper Piston assembly is installed as an upgrade, arrange the parts, including the **required** Super Deluxe C2 compression and rebound damper shim tunes. Do NOT assemble Super Deluxe C1 compression and rebound damper shim tunes with the Super Deluxe C2 High Flow Damper Piston assembly. Refer to the RockShox Spare Parts Catalog for available and required kits.



Super Deluxe (C1) Rebound Tunes - Linear, Linear H, Linear L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune.


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - Linear



Rebound Tune - Linear H



Rebound Tune - Linear L




Super Deluxe (C1) Rebound Tunes - Digressive, Progressive


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston bolt. Then continue reassembly with the compression tune.



Rebound Tune - Digressive



Rebound Tune - Progressive



Super Deluxe (C1) Compression Tunes - LC, L1, L


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm




Compression Tune - LC



Shim Quantity	x3	x4	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L1



Shim Quantity	x3	x3	x1	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L



Shim Quantity	x4	x2	x1	x1	x3
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Super Deluxe (C1) Compression Tunes - M, H


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm



Compression Tune - M



Shim Quantity	x1	x3	x1	x1	x4
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>

Compression Tune - H



Shim Quantity	x4	x2	x1	x5
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>


Super Deluxe (C2)

RS-SDLX-UFA-C2 / RS-SDLX-ULT-C2 / RS-SDLX-SELP-C2 / RS-SDLX-SEL-C2 / RS-SDLX-BSE-C2

Exploded View - Super Deluxe (C2)

Refer to the exploded view images to reference part orientation and assembly order.

Super Deluxe C1 (upgrade): If the Super Deluxe C2 High Flow Damper Piston assembly is installed as an upgrade, arrange the parts, including the **required** Super Deluxe C2 compression and rebound damper shim tunes. Do NOT assemble Super Deluxe C1 compression and rebound damper shim tunes with the Super Deluxe C2 High Flow Damper Piston assembly. Refer to the RockShox Spare Parts Catalog for available and required kits.



Super Deluxe (C2) Rebound Check Tunes - R25, R53, R55

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound check tune shim to the left of the arrow below. Then continue reassembly with the rebound tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm



Rebound Check Tune - R25



Shim Quantity	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.1</u>	<u>0.3</u>	<u>0.2</u>

Rebound Check Tune - R53



Shim Quantity	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.1</u>	<u>0.2</u>	<u>0.3</u>

Rebound Check Tune - R55




Shim Quantity	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.1</u>	<u>0.2</u>	<u>0.3</u>

Super Deluxe (C2) Rebound Check Tunes - R85

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound check tune shim to the left of the arrow below. Then continue reassembly with the rebound tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Check Tune - R85




Shim Quantity	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.1</u>	<u>0.3</u>	<u>0.2</u>


Super Deluxe (C2) Rebound Tunes - R25, R53, R55

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Tune - R25



Shim Quantity	x1	x3	x3	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

Rebound Tune - R53



Shim Quantity	x2	x2	x2	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>

Rebound Tune - R55




Shim Quantity	x3	x2	x2	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>


Super Deluxe (C2) Rebound Tunes - R85

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - R85




Super Deluxe (C2) Compression Tunes - C26, C30, C34

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C26




Shim Quantity	x2	x3	x1	x2	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - C30



Shim Quantity	x4	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - C34




Shim Quantity	x2	x2	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.15</u>


Super Deluxe (C2) Compression Tunes - C37, C40, C43

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - C37




Shim Quantity	x1	x2	x1	x1	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.15</u>	

Compression Tune - C40



Shim Quantity	x3	x1	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.2</u>	

Compression Tune - C43






Shim Quantity	x1	x2	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.3</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.2</u>

Super Deluxe Coil (A2)

RS-SDLC-ULTR-A2 / RS-SDLC-ULT-A2 / RS-SDLC-ULDH-A2 / RS-SDLC-SELP-A2 / RS-SDLC-SEL-A2

Exploded View - Super Deluxe Coil (A2)

Refer to the exploded view images to reference part orientation and assembly order.




Super Deluxe Coil (A2) Rebound Check Plate and Rebound Check Shims


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the piston nut. Then continue reassembly with the corresponding rebound tune on the following page.

If switching rebound tunes, the rebound tune must be matched with the rebound check tune. For example, if a standard rebound tune (L, M, H) is changed to a linear rebound tune (LNL, LNM, LN), install a linear rebound check tune.


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Rebound Check Tune for L, M, H Rebound Tunes






Rebound Check Tune for Linear L (LNL), Linear M (LNM), Linear (LN) Rebound Tunes



Super Deluxe Coil (A2) Rebound Tunes - L, M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the rebound shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Stack the rebound tune shims onto a hex wrench/pick, starting with the rebound tune shim to the left of the rebound check plate (flat side). Then continue reassembly with the compression tune.

Consult the *Super Deluxe Coil (A2) Rebound Check Plate and Shim Stacks* section to identify the corresponding rebound check tune.




Super Deluxe Coil (A2) Rebound Tunes - Linear L (LNL), Linear M (LNM), Linear (LN)

Print this page at 100% scale and use the shim stack specification guide below to arrange the rebound shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Stack the rebound tune shims onto a hex wrench/pick, starting with the rebound tune shim to the left of the rebound check plate (flat side). Then continue reassembly with the compression tune.


*Consult the *Super Deluxe Coil (A2) Rebound Check Plate and Shim Stacks* section to identify the corresponding rebound check tune.




Rebound Tune - Linear L (LNL)



Rebound Tune - Linear M (LNM)




Rebound Tune - Linear (LN)



Super Deluxe Coil (A2) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - LC



Shim Quantity	x5	x1	x1	x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>	

Compression Tune - L1



Shim Quantity	x5	x2	x1	x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>	

Compression Tune - L




Shim Quantity	x1	x3	x1	x2	x1	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.3</u>	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>


Super Deluxe Coil (A2) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - M



Compression Tune - H




Super Deluxe Coil (B1)

RS-SDLC-ULT-B1 / RS-SDLC-ULDH-B1 / RS-SDLC-SELP-B1 / RS-SDLC-SEL-B1

Exploded View - Super Deluxe Coil (B1)


Refer to the exploded view images to reference part orientation and assembly order.



Super Deluxe Coil (B1) Rebound Tunes - Linear, Progressive

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - Linear



Shim Quantity	x4	x3	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - Progressive




Shim Quantity	x1	x1	x1	x3	x3	x2	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>


Super Deluxe Coil (B1) Compression Tunes - LC, L1, L

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - LC



Shim Quantity	x8	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - L1



Shim Quantity	x1	x5	x2	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - L




Shim Quantity	x1	x4	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Super Deluxe Coil (B1) Compression Tunes - M, H

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - M



Shim Quantity	x5	x1	x1	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - H




Shim Quantity	x3	x2	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Vivid (C1)

RS-VIVD-UFA-C1 / RS-VIVD-UDH-C1 / RS-VIVD-ULT-C1 / RS-VIVD-SELP-C1 / RS-VIVD-SEL-C1 / RS-VIVD-BSE-C1

Exploded View - Vivid (C1)


Refer to the exploded view images to reference part orientation and assembly order.




Vivid (C1) Rebound Check Tunes - R23, R25, R53

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Check Tune - R23




Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R25



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R53




Shim Quantity	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>


Vivid (C1) Rebound Check Tunes - R54, R55, R85

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Check Tune - R54



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R55



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R85




Shim Quantity	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.1</u>	<u>0.305</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Vivid (C1) Rebound Tunes - R23, R25, R53

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - R23




Shim Quantity	x1	x1	x1	x3	x3	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - R25



Shim Quantity	x1	x1	x1	x3	x3	x2	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - R53



Shim Quantity	x7	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Vivid (C1) Rebound Tunes - R54, R55, R85


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm



Rebound Tune - R54




Shim Quantity	x1	x1	x1	x2	x1	x4	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.1</u>	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>

Rebound Tune - R55



Shim Quantity	x4	x3	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - R85



Shim Quantity	x1	x1	x1	x1	x1	x5	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.4</u>	<u>0.1</u>	<u>0.15</u>	<u>0.15</u>	<u>0.3</u>	<u>0.2</u>

Vivid (C1) Compression Tunes - C22, C26

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm




Compression Tune - C22



Shim Quantity	x9	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - C26




Shim Quantity	x8	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>

Vivid (C1) Compression Tunes - C30, C34, C37

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - C30



Shim Quantity	x1	x5	x2	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>	

Compression Tune - C34



Shim Quantity	x1	x4	x2	x2	x1	x1	x1	
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	

Compression Tune - C37




Shim Quantity	x5	x1	x1	x2	x1	x1	x1	
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	


Vivid (C1) Compression Tunes - C40, C43

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C40




Compression Tune - C43



Vivid Ultimate Flight Attendant (C1) Compression Tunes - C22, C26

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - C22



Shim Quantity	x8	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - C26




Shim Quantity	x5	x2	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>


Vivid Ultimate Flight Attendant (C1) Compression Tunes - C30, C34, C37

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - C30



Shim Quantity	x1	x4	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - C34



Shim Quantity	x5	x1	x1	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - C37




Shim Quantity	x3	x1	x1	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>


Vivid Ultimate Flight Attendant (C1) Compression Tunes - C40, C43

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C40



Compression Tune - C43




Vivid Coil (C1)

RS-VIVC-UFA-C1 / RS-VIVC-UDH-C1 / RS-VIVC-ULT-C1 / RS-VIVC-SELP-C1 / RS-VIVC-SEL-C1 / RS-VIVC-BSE-C1

Exploded View - Vivid Coil (C1)


Refer to the exploded view images to reference part orientation and assembly order.




Vivid Coil (C1) Rebound Check Tunes - R23, R25, R53

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Check Tune - R23




Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R25



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R53




Shim Quantity	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>


Vivid Coil (C1) Rebound Check Tunes - R54, R55, R85

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Check Tune - R54



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R55



Shim Quantity	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Rebound Check Tune - R85




Shim Quantity	x1	x1	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.1</u>	<u>0.305</u>	<u>0.1</u>	<u>0.15</u>	<u>0.2</u>

Vivid Coil (C1) Rebound Tunes - R23, R25, R53

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Rebound Tune - R23



Shim Quantity	x1	x1	x1	x3	x3	x2	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>

Rebound Tune - R25



Shim Quantity	x1	x1	x1	x3	x3	x2	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.1</u>	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - R53



Shim Quantity	x7	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Vivid Coil (C1) Rebound Tunes - R54, R55, R85


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Reassemble the piston assembly on the hex wrench/pick, starting with the rebound tune shim to the left of the arrow below. Then continue reassembly with the compression tune on the following page.

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm



Rebound Tune - R54




Shim Quantity	x1	x1	x1	x2	x1	x4	x1	x1
Shim Thickness (mm)	<u>0.15</u>	<u>0.1</u>	<u>0.3</u>	<u>0.15</u>	<u>0.1</u>	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>

Rebound Tune - R55



Shim Quantity	x4	x3	x1	x2
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.3</u>

Rebound Tune - R85



Shim Quantity	x1	x1	x1	x1	x1	x5	x1
Shim Thickness (mm)	<u>0.1</u>	<u>0.4</u>	<u>0.1</u>	<u>0.15</u>	<u>0.15</u>	<u>0.3</u>	<u>0.2</u>

Vivid Coil (C1) Compression Tunes - C22, C26

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)

100 mm




Compression Tune - C22



Shim Quantity	x9	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.1</u>	<u>0.1</u>	<u>0.1</u>




Compression Tune - C26



Shim Quantity	x8	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>

Vivid Coil (C1) Compression Tunes - C30, C34, C37


Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).




Vivid Coil (C1) Compression Tunes - C40, C43

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C40




Compression Tune - C43



Vivid Coil Ultimate Flight Attendant (C1) Compression Tunes - C22, C26

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - C22



Shim Quantity	x8	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>

Compression Tune - C26




Shim Quantity	x5	x2	x1	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.1</u>	<u>0.15</u>


Vivid Coil Ultimate Flight Attendant (C1) Compression Tunes - C30, C34, C37

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).

Inner Diameter (ID:mm)
Outer Diameter (OD:mm)




Compression Tune - C30



Shim Quantity	x1	x4	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.3</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - C34



Shim Quantity	x5	x1	x1	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>

Compression Tune - C37




Shim Quantity	x3	x1	x1	x2	x2	x1	x1	x1
Shim Thickness (mm)	<u>0.2</u>	<u>0.15</u>	<u>0.2</u>	<u>0.2</u>	<u>0.15</u>	<u>0.15</u>	<u>0.1</u>	<u>0.15</u>


Vivid Coil Ultimate Flight Attendant (C1) Compression Tunes - C40, C43

Print this page at 100% scale and use the shim stack specification guide below to arrange the shim stack for the desired tune. Refer to the exploded view images to reference part orientation and assembly order. Continue to reassemble the piston assembly on the hex wrench/pick, starting with the compression tune shim to the left of the piston (compression side).


Inner Diameter (ID:mm)
Outer Diameter (OD:mm)



Compression Tune - C40



Compression Tune - C43





ASIAN HEADQUARTERS

SRAM Taiwan
No. 1598-8 Chung Shan Road
Shen Kang Hsiang, Taichung City
Taiwan

WORLD HEADQUARTERS

SRAM, LLC
1000 W. Fulton Market, 4th Floor
Chicago, Illinois 60607
U.S.A.

EUROPEAN HEADQUARTERS

SRAM Europe
Paasbosweg 14-16
3862ZS Nijkerk
The Netherlands